

Platform

0.91 m x 2.44 m rear entry platform

Multiple function operation

Full proportional drive, main lift, tower lift, swing, main telescope & tower telescope control joysticks

Selectable creep speed on drive / lift and swing functions

165 degree powered platform rotator

Load sensing system

AC power cable to platform

Power & Transmission

Cummins QSB4.5-NA(60 kW) diesel engine

Four wheel drive

Four wheel steer/Two wheel steer/Crab steer

Horn

Functional Equipment & Accessories

5 degree tilt alarm and indicator light

445/65R22.5 foam filled tyres

Extending axles

Lifting/tie down lugs

Hour meter

Ground control selector switch with key lock

12V-DC auxiliary power

¹ Includes all-motion alarm and flashing amber beacon.

² Includes platform mounted work lights and head & tail lights.

³ Includes console cover, boom wipers and cylinder bellows. Available Options

Available Options

Spark arresting type muffler

All motion alarm

Alarm package ¹

Light package ²

Head and tail lights

Flashing amber beacon

Hostile environment package ³

Catalytic purifier muffler

Soft Touch proximity system



JLG Industries Inc.
Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Tel: +31 (0)23 565 5665
Fax: +31 (0)23 557 2493
e-mail address: europe@jlg.com
www.jlgeurope.com
An Oshkosh Corporation Company

Printed in UK
FORM No.: DS007-0208-500
PART NO.: DS007-ENGLISH



150HAX

Platform height	45.74 m
Horizontal outreach	24.15 m
Up and over Height	24.41 m
Swing (continuous)	360°
Platform capacity – unrestricted	230 kg
Platform rotator (hydraulic)	165°
A. Platform size	0.91 m x 2.44 m
B. Overall width (axles retracted)	3.51 m
C. Overall width (axles extended)	5.49 m
D. Tailswing (working condition)	Zero
E. Stowed height	4.27 m
F. Stowed length	12.01 m
G. Wheelbase	5.49 m
H. Ground clearance	0.28 m
Machine weight ¹	26,500 kg
Maximum ground bearing pressure	8.4 kg/cm ²
Maximum tyre load	12,000 kg
Drive speed	4.3 km/h
Gradeability	31%
Tyres	445/65R22.5 Foam Filled
Turning radius (inside) - axles retracted	4.52 m
Turning radius (inside) - axles extended	4.45 m
Turning radius (outside) - axles retracted	8.23 m
Turning radius (outside) - axles extended	9.17 m
Diesel engine – Cummins QSB4.5-NA	60 kW
Fuel tank capacity	257 L
Hydraulic system	712 L
Auxiliary sower	12V DC

¹ Certain options or country standards may increase weight and/or dimensions.

